

Splitters

Precision Group offers many solutions for Fiber Optic Splitters. We have BARE PLC splitters for in the splice case, BARE with connectors for Pedestal or NID applications, LGX Style with or without pigtailed, and ABS style which now can be rack-mounted (6 in 1RU or 12 in 2RU). We also have our new line of Flex Fiber Panels allowing for the highest-density splitter panels on the market.

Bare Fiber PLC Splitters


PFBARE



- ✓ Low Insertion Loss
- ✓ Low PDL (Polarization Dependent Loss)
- ✓ Compact Design
- ✓ Exceptional Reliability and Stability
- ✓ Wide Operating Wavelength: From 1260nm to 1650nm
- ✓ Wide Operating Temperature: From -20°C to 80°C
- ✓ Conformed to RoHS

Bare Fiber PLC Splitters with Connectors

PFBARE-C



- ✓ Low Insertion Loss
- ✓ Low PDL (Polarization Dependent Loss)
- ✓ Compact Design
- ✓ Exceptional Reliability and Stability
- ✓ Wide Operating Wavelength: From 1260nm to 1650nm
- ✓ Wide Operating Temperature: From -20°C to 80°C
- ✓ Conformed to RoHS

Precision Ruggedized ABS Splitter


PFABS



- ✓ Low Insertion Loss
- ✓ Low PDL (Polarization Dependent Loss)
- ✓ Compact Design
- ✓ Exceptional Reliability and Stability
- ✓ Wide Operating Wavelength: From 1260nm to 1650nm
- ✓ Wide Operating Temperature: From -20°C to 80°C
- ✓ Conformed to RoHS

Rack Mount PLC Splitters

PFRACK



- ✓ Low Insertion Loss
- ✓ Low PDL (Polarization Dependent Loss)
- ✓ Compact Design
- ✓ Exceptional Reliability and Stability
- ✓ Wide Operating Wavelength: From 1260nm to 1650nm
- ✓ Wide Operating Temperature: From -20°C to 80°C
- ✓ Conformed to RoHS

PRECISION GROUP

Splitters

Precision Group offers many solutions for Fiber Optic Splitters. We have BARE PLC splitters for in the splice case, BARE with connectors for Pedestal or NID applications, LGX Style with or without pigtailed, and ABS style which now can be rack-mounted (6 in 1RU or 12 in 2RU). We also have our new line of Flex Fiber Panels allowing for the highest-density splitter panels on the market.

LGX Style PLC Splitters



PFLGX

- ✓ Low Insertion Loss
- ✓ Low PDL (Polarization Dependent Loss)
- ✓ Compact Design
- ✓ Exceptional Reliability and Stability
- ✓ Wide Operating Wavelength: From 1260nm to 1650nm
- ✓ Wide Operating Temperature: From -20°C to 80°C
- ✓ Conformed to RoHS

PRECISION GROUP