Compare Our NIDs

The Precision Group NID line offers enhanced ease, speed, and efficiency for installers, coupled with a visually appealing aesthetic at the customer's premise. Our NIDs are thoughtfully designed by installers, for installers ensuring a seamless user experience and reduced deployment time ... problem solved.

Compact Flex NID (C-FLEX)

PFCFLEX-NID

- Dimensions: 7.6"Hx4"Wx2"D
- Optional Laser Engraved Logo
- Precision External Location Lug
- Optional Flex-Lock Multiport Fiber And Microduct Grommets
- Optional Riser Conduit Grommet
- Multifunctional Ground And Strength Member Securement Lug
- ✓ Flex-Lock Lay-In Cable Entry/Exit Grommets Secure And Seal Flat And Round Drop Cable
- Pole Or Wall Mount
- ✓ Low Profile Design For Customer Pleasing Aesthetics
- ✓ Integrated Slack Storage For 3.0mm Or 4.8mm I/O Cable

Standard Flex NID (FlexNID)



PFFLEX-NID

- Dimensions: 10.2"Hx10.6"Wx3"D
- **Optional Laser Engraved Logo**
- Precision External Location Lug
- Optional Flex-Lock Multiport Fiber And **Microduct Grommets**
- **Optional Riser Conduit Grommet**
- Multifunctional Ground And Strength Member Securement Lug
- ✓ Flex-Lock Lay-In Cable Entry/Exit Grommets Secure And Seal Flat And Round Drop Cable
- Splice Tray Locks In Open Position For Installer Access
- Field Selectable Bulkhead Positions
- Channel Separation For Drop And I/O Fiber

Midsized Flex NID (M-FLEX)

M-FLEXNID

- Dimensions: 9"Hx6.15"Wx2.25"D
- Optional Laser Engraved Logo
- Precision External Location Lug
- Optional Flex-Lock Multiport Fiber And Microduct Grommets
- **Optional Riser Conduit Grommet**
- Multifunctional Ground And Strength Member Securement Lug
- Flex-Lock Lay-In Cable Entry/Exit Grommets Secure And Seal Flat And Round Drop Cable
- Pole Or Wall Mount
- ✓ Field Selectable Bulkhead Positions
- ✓ Holds Up To 4 SC Or 8 LC Bulkhead Adapters
- Precision Flex Clips Offer 3 Channel Separation Of Strength Member, Buffer Tube And I/O Fiber
- Store Over 50 Feet Of 3.0mm I/O Fiber

FlexMax NID w/ **Fixed Splice Tray**

PFFIXFLEX-NID

- Dimensions: 10.2"Hx10.6"Wx3"D
- **Optional Laser Engraved Logo**
- Precision External Location Lug
- Optional Flex-Lock Multiport Fiber And Microduct Grommets
- **Optional Riser Conduit Grommet**
- Multifunctional Ground And Strength Member Securement Lug
- Flex-Lock Lay-In Cable Entry/Exit Grommets Secure And Seal Flat And Round Drop Cable
- Holds Up To 4 SC Or 8 LC Bulkhead Adapters
- ✓ Field Selectable Bulkhead Positions
- Precision Flex Clips Offer 3 Channel Separation Of Strength Member, Buffer Tube And I/O Fiber
- ✓ Store Over 100' Of 3.0mm I/O Jumper
- Fixed Splice Tray Holds Up To 12 Splices And Optional PLC Splitter

PRECISION GROUP





Compare Our NIDs

The Precision Group NID line offers enhanced ease, speed, and efficiency for installers, coupled with a visually appealing aesthetic at the customer's premise. Our NIDs are thoughtfully designed by installers, for installers ensuring a seamless user experience and reduced deployment time ... problem solved.

ONT NID (Optical Network Terminal)



PF-ONT-NID

- Dimensions 10"Wx12¾"Lx3¾"D
- ✓ Optional Laser Engraved Logo
- Fiber Splice Tray
- 2 SCA Bulkhead Adapters
- Fiber Securement
- Grounding Hardware
- Entry/Exit Grommets

Deep Base Flex NID (MFLEX-DB)

MFLEX-DB

- ✓ Dimensions: 9.88″Hx6.61"Wx3.00"D
- Optional Laser Engraved Logo
- Precision External Location Lug
- ✔ Multifunctional Ground And Strength Member Securement Lug
- ✓ Flex-Lock Lay-In Cable Entry/Exit Grommets Secure And Seal Flat And Round Drop Cable
- ✓ Optional Flex-Lock Multiport Fiber And Microduct Grommets
- ✓ Optional Riser Conduit Grommet

Pole Or Wall Mount

- ✓ Field Selectable Bulkhead Positions
- ✓ Holds Up To 4 SC Or 8 LC Bulkhead Adapters
- Precision Flex Clips Offer 3 Channel Separation Of Strength
 Member, Buffer Tube And I/O Fiber
- Store Over 50 Feet Of 3.0mm I/O Fiber or up to 150ft of 3.0mm I/O fiber on a spool
- Push-Through Grommets
- Flat-Drop Channel for Aerial Applications
- ✓ Toolless Clear Splice Tray Cover
- ✓ Additional Internal & External Mounting Holes

Dimensions: 10.3 H x 10.8" W x 4.4" D Optional Laser Engraved Logo

PF-FLEXMXU

Flex MXU NID

- Precision External Location Lug
- Optional Flex-Lock Multiport Fiber And Microduct Grommets
- Optional Riser Conduit Grommet
- Multifunctional Ground And Strength Member Securement Lug
- Flex-Lock Lay-In Cable Entry/Exit Grommets Secure And Seal Flat And Round Drop Cable
- ✓ Holds Up To 12 SC Bulkhead Adapters
- ✓ Precision Flex Clips Offer 3 Channel
- Separation Of Strength Member, Buffer Tube
 And I/O Fiber
- ✓ Store Over 100' Of 3.0mm I/O Jumper
- Fixed Splice Tray Holds Up To 16 Splices And Optional PLC Splitter

PRECISION GROUP

