Compare Our NIDs

The Precision Group NID line offers enhanced ease, speed, and efficiency for installers, coupled with a visually appealing aesthetic at the customer's premise. Our NIDs are thoughtfully designed by installers, for installers ensuring a seamless user experience and reduced deployment time ... problem solved.

Compact Flex NID (C-FLEX)

PFCFLEX-NID

- ✓ Dimensions: 7.6"Hx4"Wx2"D
- Optional Laser Engraved Logo
- ✓ Precision External Location Lug
- ✓ Optional Flex-Lock Multiport Fiber And Microduct Grommets
- Optional Riser Conduit Grommet
- Multifunctional Ground And Strength Member Securement Lug
- ✓ Flex-Lock Lay-In Cable Entry/Exit Grommets Secure And Seal Flat And Round Drop Cable
- ✓ Pole Or Wall Mount
- ✓ Low Profile Design For Customer Pleasing Aesthetics
- ✓ Integrated Slack Storage For 3.0mm Or 4.8mm I/O Cable

Standard Flex NID (FlexNID)

PFFLEX-NID




- ✓ Dimensions: 10.2"Hx10.6"Wx3"D
- Optional Laser Engraved Logo
- Precision External Location Lug
- Optional Flex-Lock Multiport Fiber And Microduct Grommets
- Optional Riser Conduit Grommet
- Multifunctional Ground And Strength Member Securement Lug
- ✓ Flex-Lock Lay-In Cable Entry/Exit Grommets Secure And Seal Flat And Round Drop Cable
- ✓ Splice Tray Locks In Open Position For


Installer Access

- Field Selectable Bulkhead Positions
- ✓ Channel Separation For Drop And I/O Fiber

Midsized Flex NID (M-FLEX)

M-FLEXNID





- ✓ Precision External Location Lug
- ✓ Optional Flex-Lock Multiport Fiber And Microduct Grommets
- Optional Riser Conduit Grommet
- Multifunctional Ground And Strength Member Securement Lug
- ✓ Flex-Lock Lay-In Cable Entry/Exit Grommets Secure And Seal Flat And Round Drop Cable
- ✓ Pole Or Wall Mount
- ✓ Field Selectable Bulkhead Positions
- ✓ Holds Up To 4 SC Or 8 LC Bulkhead Adapters
- ✓ Precision Flex Clips Offer 3 Channel Separation Of Strength Member, Buffer Tube And I/O Fiber
- Store Over 50 Feet Of 3.0mm I/O Fiber

FlexMax NID w/ Fixed Splice Tray

PFFIXFLEX-NID



- ✓ Dimensions: 10.2"Hx10.6"Wx3"D
- ✓ Optional Laser Engraved Logo
- ✓ Precision External Location Lug
- Optional Flex-Lock Multiport Fiber And Microduct Grommets
- Optional Riser Conduit Grommet
- Multifunctional Ground And Strength Member Securement Lug
- ✓ Flex-Lock Lay-In Cable Entry/Exit Grommets Secure And Seal Flat And Round Drop Cable
- ✓ Holds Up To 4 SC Or 8 LC Bulkhead Adapters
- ✓ Field Selectable Bulkhead Positions
- ✓ Precision Flex Clips Offer 3 Channel Separation Of
 - Strength Member, Buffer Tube And I/O Fiber
- ✓ Store Over 100' Of 3.0mm I/O Jumper
- ✓ Fixed Splice Tray Holds Up To 12 Splices And Optional PLC Splitter




Compare Our NIDs

The Precision Group NID line offers enhanced ease, speed, and efficiency for installers, coupled with a visually appealing aesthetic at the customer's premise. Our NIDs are thoughtfully designed by installers, for installers ensuring a seamless user experience and reduced deployment time ... problem solved.

ONT NID (Optical Network Terminal)







- Dimensions 10"Wx1234"Lx334"D
- ✓ Optional Laser Engraved Logo
- ✓ Fiber Splice Tray
- ✓ 2 SCA Bulkhead Adapters
- ✓ Fiber Securement
- ✓ Grounding Hardware
- Entry/Exit Grommets

Flex MXU NID

PF-FLEXMXU





- Precision External Location Lug
- Optional Flex-Lock Multiport Fiber And Microduct Grommets
- Optional Riser Conduit Grommet
- Multifunctional Ground And Strength Member Securement Lug
- Flex-Lock Lay-In Cable Entry/Exit Grommets Secure And Seal Flat And Round Drop Cable
- ✓ Holds Up To 12 SC Bulkhead Adapters
- ✓ Precision Flex Clips Offer 3 Channel
- Separation Of Strength Member, Buffer Tube And I/O Fiber
- ✓ Store Over 100' Of 3.0mm I/O Jumper
- ✓ Fixed Splice Tray Holds Up To 16 Splices And Optional PLC Splitter



Compare Our NIDs

The Precision Group NID line offers enhanced ease, speed, and efficiency for installers, coupled with a visually appealing aesthetic at the customer's premise. Our NIDs are thoughtfully designed by installers, for installers ensuring a seamless user experience and reduced deployment time ... problem solved.

Midsized Deep Base FlexNID (MFLEX-DB) Non Spool Compatible

MFLEX-DB

- Dimensions: 9.88"Hx6.61"Wx3.00"D
- Optional Laser Engraved Logo
- Precision External Location Lug
- Multifunctional Ground And Strength Member Securement Lug
- Flex-Lock Lay-In Cable Entry/Exit Grommets Secure And Seal Flat And Round Drop Cable
- Optional Flex-Lock Multiport Fiber And Microduct Grommets
- Optional Riser Conduit Grommet
- Pole Or Wall Mount
- ✓ Field Selectable Bulkhead Positions
- ✓ Holds Up To 4 SC Or 8 LC Bulkhead Adapters
- Precision Flex Clips Offer 3 Channel Separation Of Strength Member, Buffer Tube And I/O Fiber
- ✓ Store Over 50 Feet Of 3.0mm I/O Fiber Push-Through Grommets For Exiting The Rear of the NID
- ✓ Flat-Drop Channel for Aerial Applications
- ✓ Tool-less Clear Splice Tray Cover
- ✓ Flexible Mounting Via Internal & External Mounting Positions
- Flex-lock Output Grommet for Dual 3.0 or 4.8mm Round I/O Jumper Standard
- ✓ Optional Microduct Grommets

Midsized Deep Base FlexNID (MFLEX-DB) **Spool Compatible**

MFLEX-DBS

- Dimensions: 9.88"Hx6.61"Wx3.00"D
- Optional Laser Engraved Logo
- Precision External Location Lug
- Multifunctional Ground And Strength Member Securement Lug
- Flex-Lock Lay-In Cable Entry/Exit Grommets Secure And Seal Flat And Round Drop Cable
- Optional Flex-Lock Multiport Fiber And Microduct Grommets
- Optional Riser Conduit Grommet
- ✓ Pole Or Wall Mount
- ✓ Field Selectable Bulkhead Positions
- ✓ Holds Up To 4 SC Or 8 LC Bulkhead Adapters
- ✓ Precision Flex Clips Offer 3 Channel Separation Of Strength Member, Buffer Tube And I/O Fiber
- ✓ Store Over 50 Feet Of 3.0mm I/O Fiber on a Spool Push-Through Grommets For Exiting The Rear of the NID
- ✓ Flat-Drop Channel for Aerial Applications
- ✓ Tool-less Clear Splice Tray Cover
- Flexible Mounting Via Internal & External Mounting Positions
- Flex-lock Output Grommet for Dual 3.0 or 4.8mm Round I/O Jumper Standard
- Optional Microduct Grommets