

FTTx Power Adapters

Precision Group's FTTx power adapters are designed to provide reliable power for ONTs and customer premise equipment across fiber broadband deployments. Built for indoor applications, these ONT power supplies support a range of connector types, voltages, and compatibility needs for residential and business installations.

FTTx ONT Power Supply, DIN Connector, Indoor

FTTXPSDIN9



- ✓ 2 prong power supplies, input voltage 100-240VAC ~50/60HZ
- ✓ 9 pin DIN connector type
- ✓ 12VDC 1.5A/18W (Max Output)
- ✓ Other wattages available upon request

FTTx ONT Power Supply, 5.5 x 2.1mm Barrel Connector, Indoor

FTTXPS5521



- ✓ Compatible with many customer premise equipment models
- ✓ 2 prong, input voltage 100-240VAC ~50/60HZ
- ✓ 12VDC 3A/36W (Max Output)
- ✓ 5.5MM X 2.1MM barrel connector type
- ✓ Compatible with ADTRAN 602X / 611 / 621 / 621I / 622V / 601 / 631 / 631QV / 632V

FTTx ONT Power Supply, 8 Pin Molex Connector, Indoor

FTTXPSMOLEX



- ✓ Compatible with Most Indoor ONT Models
- ✓ 2 Prong, Input Voltage 100-240VAC ~50/60Hz
- ✓ 12VDC 3A/36W (Max Output)
- ✓ 8 Pin Molex Connector Type

FTTx ONT Power Supply, 5.5 x 2.5mm Barrel Connector, Indoor

FTTXPS5525



- ✓ Compatible with customer premise equipment models with 5.5 x 2.5MM barrel connectors
- ✓ 2 prong, input voltage 100-240VAC ~50/60HZ
- ✓ 12VDC 2.5A/30W (Max Output)
- ✓ 5.5MM x 2.5MM barrel connector type
- ✓ Compatible with CALIX 801G / 803G / 844E / GP1100X / GP1101X / 4200A / U4 / U6XW / U10XW / 7U10



(888) 619-1651
Sales@GoPrecisionGroup.com
GoPrecisionGroup.com

FTTx Power Adapters

Precision Group's FTTx power adapters are designed to provide reliable power for ONTs and customer premise equipment across fiber broadband deployments. Built for indoor applications, these ONT power supplies support a range of connector types, voltages, and compatibility needs for residential and business installations.

FTTx ONT Power Supply, USB-C 45W, Indoor

PP45USBCPD3.0-6



- ✓ USB-C Power Delivery (PD) support for dynamic voltage and current negotiation
- ✓ 45W maximum power output
- ✓ Single, flexible power solution to reduce model-specific adapters
- ✓ 100–240VAC input voltage (50–60HZ)
- ✓ Compact indoor form factor

FTTx OLT Power Supply, 48V 250W, Indoor

PP250PB-48



- ✓ 48V 250 watt power brick
- ✓ Reliable, low cost power only option for network access equipment or OLT's
- ✓ Passive cooling, no moving parts or fan
- ✓ 4 ft detachable AC power cord
- ✓ 6 ft DC power cord to equipment

3-Outlet Power Strip, Indoor

PP3P16-PS-3



- ✓ Reliable Power to Customer Premise Equipment
- ✓ 15-amp power strip equipped with 3 three-prong outlets
- ✓ 3-foot cord for flexible positioning and reach
- ✓ Keyhole wall mounting slots
- ✓ Compact design fits easily behind furniture and in tight spaces

6-Outlet Power Strip, Indoor

PP6P14-PS-3-D90



- ✓ Reliable Power to Customer Premise Equipment
- ✓ 15-amp power strip equipped with 6 three-prong outlets
- ✓ 3-foot cord for flexible positioning and reach
- ✓ Keyhole wall mounting slots
- ✓ Compact design fits easily behind furniture and in tight spaces
- ✓ Integrated On/Off switch



(888) 619-1651
Sales@GoPrecisionGroup.com
GoPrecisionGroup.com