

Micro Drop – Connectorized Drops

The Precision Fiber Micro Drop is a Lower Profile version of our Flat Drop Product Offering. Precision Micro Drop will allow users to fit more drops in a smaller space. It's low profile also makes it more flexible for easier pulling and cable management. PFMD is available in multiple lengths. It can be connectorized on one or both ends with Corning Optical Communications LLC Optitap® Compatible, SC or LC connectors. Available in both Toneable and Non-Tunable versions to support Underground or Aerial installations.



FEATURES

BUILT WITH A2 BEND INSENSITIVE FIBER

COMPATIBLE WITH CORNING OPTICAL COMMUNICATIONS LLC OPTITAP® COMPATIBLE, SC OR LC CONNECTORS

TONEABLE OPTION

AVAILABLE WITH 4.8MM BREAKOUT ON CONNECTORIZED ENDS

PULL SOCKS AND REEL OPTIONS AVAILABLE

SPECIFICATIONS

Reel Size: 400 mm

Hole Size: 160 mm

Inner Height: 230 (-0, +5) mm

Thickness: 18mm

Package Size: 410*285*410mm

Pallet Size: 1.25*0.9*2.17m/45cartons

*900 micron tight buffer for easy splice prep

Micro Drop – Connectorized Drops

ORDERING GUIDE

Example Part Number: PMD-OTC-SCA-3B-X-100F

